

ROUGH TERRAIN (2.5T – 3T)

FORKLIFT SPECIFICATION



MODEL	CPCD25RT	CPCD30RT
LOAD CAPACITY	2500KG	3000KG
LOAD CENTRE	500MM	500MM
POWER TYPE	DIESEL	DIESEL
MAX LIFTING SPEEDS (WITH LOAD) MM/S	545	440
MAX DRIVING SPEEDS (WITH LOAD) MM/S	21 KM / HR	21 KM / HR
LIFTING HEIGHT	3000MM	3000MM
TILTING ANGLES (FORWARD / BACKWARD) *	6/12	6/12
MIN TURNING RADIUS	2950MM	3000MM
DEPARTURE ANGLE (*)	32	30
MIN GROUND CLEARANCE	290MM	320MM
OVERALL LENGTH (INCLUDING FORK)	4010MM	4260MM
OVERALL WIDTH	1565MM	1620MM
OVERALL HEIGHT (MAST LOWERED)	2280MM	2320MM
OVERALL HEIGHT (MAST EXTENDED)	4065MM	4270MM
OVERALL HEIGHT TO OVERHEAD GUARD	2270MM	2315MM
FRONT OVERHANG (MM)	550	590
WHEELBASE (MM)	1800	1850
FRONT WHEEL (MM)	1240	1250
REAR WHEEL (MM)	1175	1175
FRONT TYRE	12-16.5-14	14-17.5-14
REAR TYRE	27* 10-12	27* 10-12
SELF WEIGHT (KGS)	4200	4700
FORK WIDTH (MM)	122	125
FORK THICKNESS (MM)	40	45
BACKREST HEIGHT (MM)	1000	1230
STANDARD FORK LENGTH (MM)	1070	1200
MODEL	CHINA	CHINA
RATED POWER (KW)	36.8	48
ROTATE SPEED @ RATED POWER RPM	2500	2300
MAX TORQUE Nm	185	250
ROTATE SPEED @ MAX TORQUE RPM	1800	1800
POWER SHIFT TYPE	TOR-CON	TOR-CON





REDLIFT



ROUGH TERRAIN (2.5T – 3T) FORKLIFT SPECIFICATION

